

15 kv  
HUBBELL

CONNECTOR 750 AWG  
HUBBELL 625LUG38

2.56" [2 9/16"]

9.71" [9 11/16"]

INSULATION CUT  
BACK TEMPLATE

6.22" [6 3/16"]

TOOL STOP

INSULATION, 220 MILS

SEMI-CON SHIELD

4.43" [4 7/16"]

10.71" [10 11/16"]  
11-10P PRE-SWAGE  
INJECTION ADAPTER (IA)

HUBBELL® T-BODY 625TB(T)

MARKING TAPE

SEMI-CON SHIELD

CABLE INSULATION  
ADAPTER 625CA-M

TOOL STOP CUT  
BACK TEMPLATE

**NOTE: THE INSULATION ADAPTER MUST  
BE ON THE CABLE BEFORE SWAGING THE  
CONNECTOR. SEE NRI 31 & NRI 32**

The marking tape must be located from end of strip cable (as shown as pre-swage) to the end of cable insulation adapter and should be within 1/4 inch [6mm] after swage.

HBL-15 625TB(T)M 750 11-10P 25mar10

© Copyright 2007, Novinium, Inc. All rights reserved.  
IA is protected by patents and patents pending

HUBBELL is a registered trademark of Hubbell Power Systems, Inc. novinium is a registered trademark of novinium.  
(Printing instructions: For best results, print in color, protect w/5mil laminate and trim to size.)



SCALE: 1:1 8.5 x 22 paper size