

15 kv  
HUBBELL

CONNECTOR 4/0 AWG  
HUBBELL 625LUG27

2.67" [2 11/16"]

6-4 PRE-SWAGE  
INJECTION ADAPTER (IA)

9.77" [9 3/4"]

INSULATION CUT  
BACK TEMPLATE

TOOL STOP

INSULATION  
220 MILS

SEMI-CON SHIELD

4.45" [4 7/16"]

10.77" [10 3/4"]

HUBBELL® T-BODY 625TB(T)

MARKING TAPE

SEMI-CON SHIELD

CABLE INSULATION  
ADAPTER 625CA-H

TOOL STOP CUT  
BACK TEMPLATE

**NOTE: THE INSULATION ADAPTER MUST  
BE ON THE CABLE BEFORE SWAGING THE  
CONNECTOR. SEE NRI 31 & NRI 32**

The marking tape must be located from end of strip cable (as shown as pre-swage) to the end of cable insulation adapter and should be within 1/4 inch [6mm] after swage.

HBL-15 625TB(T)H 40 6-4 25mar10

© Copyright 2007, Novinium, Inc. All rights reserved.  
IA is protected by patents and patents pending

HUBBELL is a registered trademark of Hubbell Power Systems, Inc. Novinium is a registered trademark of Novinium.  
(Printing Instructions: For best results, print in color, protect w/5mil laminate and trim to size.)



SCALE: 1:1

8.5 x 22 paper size