

15 KV  
HUBBELL

CONNECTOR 500 AWG  
HUBBELL 625LUG33

2.69" [2 11/16"]

9.77" [9 3/4"]

10-8 PRE-SWAGE (IA)  
INJECTION ADAPTER

INSULATION CUT  
BACK TEMPLATE

SEMI-CON SHIELD

INSULATION  
220 MILS

TOOL STOP

4.44" [4 7/16"]

6.30" [6 5/16"]

10.77" [10 3/4"]

MARKING TAPE

HUBBELL® T-BODY 625TB(T)

SEMI-CON SHIELD

CABLE INSULATION  
ADAPTER 625CA-L

TOOL STOP CUT  
BACK TEMPLATE

**NOTE: THE INSULATION ADAPTER MUST  
BE ON THE CABLE BEFORE SWAGING THE  
CONNECTOR. SEE NRI 31 & NRI 32**

The marking tape must be located from end of strip cable (as shown as pre-swage) to end of cable insulation adapter and should be within 1/4" inch [6mm] after swage.

HBL-15 625TB(T)L 500 10-8 25mar10

© Copyright 2007, Novinium, Inc. All rights reserved.  
IA is protected by patents and patents pending  
HUBBELL is a registered trademark of Hubbell Power Systems, Inc. Novinium is a registered trademark of Novinium.  
(Printing instructions: For best results, print in color, protect w/5mil laminate and trim to size.)



SCALE: 1:1 8.5 x 22 paper size