

25 KV

HUBBELL

CONNECTOR 250 AWG
HUBBELL 625LUG28

2.58" [2 9/16"]

7-6 PRE-SWAGE (IA)
INJECTION ADAPTER

9.74" [9 3/4"]

INSULATION CUT
BACK TEMPLATE

4.45" [4 7/16"]

TOOL STOP

6.21" [6 3/16"]

10.74" [10 3/4"]

INSULATION
260 MILS

SEMI-CON SHIELD

HUBBELL® T-BODY 625TB(T)

MARKING TAPE

SEMI-CON SHIELD

CABLE INSULATION
ADAPTER 625CA-J

TOOL STOP CUT
BACK TEMPLATE

**NOTE: THE INSULATION ADAPTER MUST
BE ON THE CABLE BEFORE SWAGING THE
CONNECTOR. SEE NRI 31 & NRI 32**

The marking tape must be located from end of strip cable (as shown as pre-swage) to the end of cable insulation adapter and should be within 1/4 inch [6mm] after swage..

HBL-25 625TB(T)J 250 7-6 25mar10

© Copyright 2007, Novinium, Inc. All rights reserved.

IA is protected by patents and patents pending

HUBBELL is a registered trademark of Hubbell Power Systems, Inc. novinium is a registered trademark of novinium.

(Printing instructions: For best results, print in color, protect w/5mil laminate and trim to size.)

SCALE: 1:1 8.5 x 22 paper size

