

15 KV
HUBBELL

CONNECTOR #2 AWG
HUBBELL 625LUG22

2.72" [2 3/4"]

9.77" [9 3/4"]

3-4 PRE-SWAGE (IA)
INJECTION ADAPTER

TOOL STOP

6.36" [6 3/8"]

10.77" [10 3/4"]

4.44" [4 7/16"]

HUBBELL® T-BODY 625TB(T)

INSULATION CUT
BACK TEMPLATE

INSULATION
220 MILS

SEMI-CON SHIELD

MARKING TAPE

SEMI-CON SHIELD

CABLE INSULATION
ADAPTER 625CA-F

TOOL STOP CUT
BACK TEMPLATE

**NOTE: THE INSULATION ADAPTER MUST
BE ON THE CABLE BEFORE SWAGING THE
CONNECTOR. SEE NRI 31 & NRI 32**

The marking tape must be located from end of strip cable (as shown as pre-swage) to end of cable insulation adapter and should be within 1/4" inch [6mm] after swage.

HBL-15 625TB(T)F #2 3-4 25mar10

© Copyright 2007, Novinium, Inc. All rights reserved.
IA is protected by patents and patents pending
HUBBELL is a registered trademark of Hubbell Power Systems Inc. Novinium is a registered trademark of Novinium.
(Printing instructions: For best results, print in color, protect w/5mil laminate and trim to size.)

Novinium

SCALE: 1:1 8.5 x 22 paper size