

HUBBELL
25 KV

CONNECTOR 1000 MCM
HUBBELL 625LUG41

3.06" [3 1/16"]

9.74" [9 3/4"]

14-10 PRE-SWAGE
INJECTION ADAPTER (IA)

INSULATION CUT
BACK TEMPLATE

4.45" [4 7/16"]

TOOL STOP

260 MILS
INSULATION

SEMI-CON SHIELD

6.69" [6 11/16"]

10.73" [10 3/4"]

HUBBELL® T-BODY 625TB(T)

MARKING TAPE

SEMI-CON SHIELD

CABLE INSULATION
ADAPTER 625CA-N

TOOL STOP CUT
BACK TEMPLATE

**NOTE: THE INSULATION ADAPTER MUST
BE ON THE CABLE BEFORE SWAGING THE
CONNECTOR. SEE NRI 31 & NRI 32**

The marking tape must be located from end of strip cable (as shown as pre-swage) to the end of cable insulation adapter and should be within 1/4 inch [6mm] after swage.

HBL-25 625TB(T)N 1000 14-10 25mar10

© Copyright 2007, Novinium, Inc. All rights reserved.

IA is protected by patents and patents pending

HUBBELL is a registered trademark of Hubbell Power Systems, Inc. Novinium is a registered trademark of Novinium. (Printing instructions: For best results, print in color, protect w/5mil laminate and trim to size.)

SCALE: 1:1

8.5 x 22 paper size

